



GEO-HB-Screw-in sockets

Connection 1	UN/UNF external threads
Sealing form 1	O-ring seal on screw-in socket
Connection 2	BSP cylindrical external threads
Sealing form 2	60° inner cone
Design	Screw-in sockets
Construction	straight
Material	Steel
Surface	electro galvanised

Name	G1	G2	OR	SW
GEO 04 HB 02	7/16-20	G 1/8"-28	8,92 x 1,83	17
GEO 04 HB	7/16-20	G 1/4"-19	8,92 x 1,83	17
GEO 04 HB 06	7/16-20	G 3/8"-19	8,92 x 1,83	21
GEO 05 HB 02	1/2-20	G 1/8"-28	10,52 x 1,83	19
GEO 05 HB 04	1/2-20	G 1/4"-14	10,52 x 1,83	19
GEO 05 HB 06	1/2-20	G 3/8"-19	10,52 x 1,83	21
GEO 06 HB 04	9/16-18	G 1/4"-19	11,90 x 1,98	21
GEO 06 HB	9/16-18	G 3/8"-19	11,90 x 1,98	21
GEO 06 HB 08	9/16-18	G 1/2"-14	11,90 x 1,98	28
GEO 08 HB 04	3/4-16	G 1/4"-19	16,36 x 2,20	26
GEO 08 HB 06	3/4-16	G 3/8"-19	16,36 x 2,20	26
GEO 08 HB	3/4-16	G 1/2"-14	16,36 x 2,20	28
GEO 08 HB 10	3/4-16	G 5/8" -14	16,36 x 2,20	30
GEO 08 HB 12	3/4-16	G 3/4"-14	16,36 x 2,20	36
GEO 10 HB 06	7/8-14	G 3/8"-19	19,18 x 2,46	30
GEO 10 HB 08	7/8-14	G 1/2"-14	19,18 x 2,46	30
GEO 10 HB	7/8-14	G 5/8" -14	19,18 x 2,46	30
GEO 10 HB 12	7/8-14	G 3/4"-14	19,18 x 2,46	36
GEO 10 HB 16	7/8-14	G 1" -11	19,18 x 2,46	40
GEO 12 HB 08	1.11/16" -12	G 1/2"-14	23,47 x 2,95	36
GEO 12 HB 10	1.11/16" -12	G 5/8" -14	23,47 x 2,95	36
GEO 12 HB	1.11/16" -12	G 3/4"-14	23,47 x 2,95	36
GEO 12 HB 16	1.11/16" -12	G 1" -11	23,47 x 2,95	45
GEO 16 HB 12	1.5/16" -12	G 3/4"-14	29,74 x 2,95	45
GEO 16 HB	1.5/16" -12	G 1" -11	29,74 x 2,95	45
GEO 16 HB 20	1.5/16" -12	G 1/1/4"-11	29,74 x 2,95	55
GEO 20 HB 16	1.5/8" -12	G 1" -11	37,47 x 3,00	55
GEO 20 HB	1.5/8" -12	G 1.1/4" -11	37,47 x 3,00	55

Name	G1	G2	OR	SW
GEO 24 HB 20	1.7/8" -12	G 1.1/4" -11	43,69 x 3,00	62
GEO 24 HB	1.7/8" -12	G 1.1/2" -11	43,69 x 3,00	62