



## Plug-in coupling sleeve (bulkhead connection) -light version

### Application

General application, e.g. in industry, construction machinery, agricultural technology etc.

### Design

Coupling with bulkhead connection

### Connection

metric cylindrical outer thread

### Sealing form

24° inner cone

### Standard

complies with ISO 7241

### Material

Steel

### Surface

electro galvanised

Name	DN	Screw	Typoszereg	do średnicy zew. rury Ø mm	Typowielkość
SKMS 04 HL 2	4	M 12x1,5	L	6	2
SKMS 06 HL 2	6	M 14x1,5	L	8	2
SKMS 06 HL 3	6	M 14x1,5	L	8	3
SKMS 08 HL 2	8	M 16x1,5	L	10	2
SKMS 08 HL 3	8	M 16x1,5	L	10	3
SKMS 10 HL 3	10	M 18x1,5	L	12	3
SKMS 10 HL 4	10	M 18x1,5	L	12	4
SKMS 13 HL 3	12	M 22x1,5	L	15	3
SKMS 13 HL 4	12	M 22x1,5	L	15	4
SKMS 16 HL 3	16	M 26x1,5	L	18	3
SKMS 16 HL 4	16	M 26x1,5	L	18	4
SKMS 16 HL 5	16	M 26x1,5	L	18	5
SKMS 20 HL 4	19	M 30x2	L	22	4
SKMS 20 HL 5	19	M 30x2	L	22	5
SKMS 25 HL 5	25	M 36x2	L	28	5