



## Plug-in coupling sleeve (bulkhead connection) -heavy version

Application

General application, e.g. in industry, construction machinery, agricultural technology etc.

Design

Coupling with bulkhead connection

Connection

metric cylindrical outer thread

Sealing form

24° inner cone

Standard

complies with ISO 7241

Material

Steel

Surface

electro galvanised

Name	DN	Screw	Typoszereg	do średnicy zew. rury Ø mm	Typowielkość
SKMS 04 HS 2	4	M 16x1,5	S	8	2
SKMS 06 HS 1	6	M 18x1,5	S	10	1
SKMS 06 HS 2	6	M 18x1,5	S	10	2
SKMS 06 HS 3	6	M 18x1,5	S	10	3
SKMS 08 HS 2	8	M 20x1,5	S	12	2
SKMS 08 HS 3	8	M 20x1,5	S	12	3
SKMS 10 HS 3	10	M 22x1,5	S	14	3
SKMS 10 HS 4	10	M 22x1,5	S	14	4
SKMS 13 HS 3	12	M 24x1,5	S	16	3
SKMS 13 HS 4	12	M 24x1,5	S	16	4
SKMS 16 HS 3	16	M 30x2	S	20	3
SKMS 16 HS 4	16	M 30x2	S	20	4
SKMS 16 HS 5	16	M 30x2	S	20	5
SKMS 20 HS 5	19	M 36x2	S	25	5
SKMS 25 HS 5	25	M 42x2	S	30	5