



Quick couplers TEMA-series TIB

Standard Nordic developed by TEMA (CEJN 525) is not compatible with ISO-A and ISO-B.

It is characterized by a large flow and a mechanism preventing accidental disconnection.

Quick couplings are also available with pressure eliminator or without valve.

Operating pressure of 250 bar.

Name	Screw	Ciśn. rob. (bar)	L1 (mm)	L2 (mm)	D1 (mm)	SW	Wersja	Uszczelnienie
TIB 2510	G1/4	400	57	12	28	24	Standard	Nitryl
TIB 2520	G1/4	400	38,0	12	22	19	Standard	Nitryl
TIB 3810	G3/8	320	63	12	34	30	Standard	Nitryl
TIB 3820	G3/8	320	42,0	12	22	24	Standard	Nitryl
TIB 5010	G1/2	320	66	14,0	39	33	Standard	Nitryl
TIB 5020	G1/2	320	48,0	14,0	31	28	Standard	Nitryl
TIB 7510	G3/4	300	81	16,0	52	46	Standard	Nitryl
TIB 7520	G3/4	300	59	16,0	39	36	Standard	Nitryl
TIB 10010	G1	300	94	18,0	62	50	Standard	Nitryl
TIB 10020	G1	300	70	18,0	46	42	Standard	Nitryl